



## Technical Product Data

- a) Product Name Asbestos Free Plaspertex Masonry Paint
- b) Reference Number P.P.01
- c) Product Description A highly decorative and protective coating. Formulated to give an asbestos free system that offers long term durability combining a high quality alkyd resin blended with a plasticiser, titanium and iron oxides are used to give excellent hiding power and pigmentation, reinforcing fibres and extenders provide the toughness and textured finish that enables the coating to withstand the elements. Dec-99
- d) Uses A high build long life interior and exterior masonry coating.
- e) Pack Sizes 25 Litres
- f) Colour Range White and 12 shades as per Plaspertex colour card
- g) Specific Gravity 1.21
- h) Flash Point Over 100°F
- i) Solids 49% by volume
- j) Spreading Rate @ D.R.A.T 1¼ litres / sq. metre = (2¾ imp. Gallons / 100 sq. ft.)
- k) Drying Time Touch dry 24 hours – Full cure 2 – 3 weeks
- l) Overcoating Time 24 hours
- m) Lowest Application Temperature 5°C
- n) Dry Recommended Application Thickness D.R.A.T 500 microns
- o) Methods of Application Spray
- p) Recommended Preparation See preparation data Sheet No 1
- q) Storage Life One Year
- r) Thinner / Cleaner White Spirit
- s) Precautions Stir well before use
- t) Safety Ensure the use of good filter masks when spraying. The use of Barrier Cream is recommended. Do not smoke or allow naked flames in vicinity of work. Extreme care must be taken when spraying in enclosed areas. Supply air fed masks.