



Technical Product Data

- a) Product Name **E.M.C.5**
- b) Reference Number **P.P.39.**
- c) Product Description **A high quality textured coating system based on a thermoplastic resin incorporating butadiene and acrylate monomers, Titanium and other pigments. Offers excellent colour retention. Various size particles of Granicalcium are used to give an extremely durable coating.**
- d) Uses **A textured long life coating for masonry substrates.**
- e) Pack Sizes **20 litres**
- f) Colour Range **12 Colours plus white**
- g) Specific Gravity **1.53**
- h) Flash Point **over 23°C**
- i) Solids **51.0**
- j) Spreading Rate @ D.R.A.T **1.25 kg / m²**
- k) Drying Time **touch dry 24 hours. Full cure 2 - 3 weeks.**
- l) Lowest Application Temperature **5°C**
- m) Dry Recommended Application Thickness D.R.A.T **295 Microns.**
- n) Methods of Application **Roller & Trowel Roller & Texturing Air Spraying Pressurised Pot**
- o) Recommended Preparation **See Preparation Data Sheet No. 7**
- p) Storage Life **12 months**
- q) Thinner / Cleaner **White Spirit**
- r) Safety **Ensure the use of good filter masks when spraying. The use of barrier cream is recommended. Do not smoke or allow naked flames in the vicinity of work. Extreme care must be taken when spraying in enclosed areas.**