



Technical Product Data

- a) Product Name **HIGHBUILD**
- b) Reference Number P.P.35.
- c) Product Description A high quality textured coating system based on a thermoplastic resin incorporating butadiene and acrylic monomers, titanium and iron oxide pigments. Offers excellent colour retention. Various size particles of granicalcium are used to give an extremely durable long-term coatings.
- d) Uses A high build long-life coating for Masonry Substrates.
- e) Pack Sizes 25 litre drums.
- f) Colour Range 11 colours plus white
- g) Specific Gravity 1.53
- h) Flash Point Over 23°C
- i) Solids 47-0
- j) Spreading Rate @ D.R.A.T 1.2 litres per Metre
- k) Drying Time Touch Dry 24 hours. Full cure 2-3 weeks
- l) Lowest Application Temperature 5°C
- m) Dry Recommended Application Thickness D.R.A.T 500 Microns
- n) Methods of Application Roller & Texturing. Air spray pressurised pot.
- o) Recommended Preparation See Preparation Sheet No 1
- p) Storage Life 12 months
- q) Thinner / Cleaner White Spirit
- r) Precautions Ensure the use of good filter masks when spraying. The use of barrier cream is recommended. Do not allow naked flames in the vicinity of work. Extreme care must be taken when spraying in enclosed areas. Supply air fed masks.