



Technical Product Data

- a) Product Name **LOWBUILD S TEXTURE**
- b) Reference Number PP47
- c) Product Description A high quality textured coating system based on a thermoplastic resin incorporating Butadiene and Acrylate Monomers, Titanium and Iron Oxide Pigments. Offers excellent colour retention. Various size particles and Granicalcium are used to give an extremely durable long term coating.
- d) Uses A textured long life coating for Masonry Substrates.
- e) Pack Sizes 15 litre drums
- f) Colour Range 6 colours plus White
- g) Specific Gravity 1.53
- h) Flash Point Over 23 degrees C.
- I) Solids by Volume 51.0
- j) Spreading Rate 1.0 kg/M2
- k) Drying Time Touch Dry 24 Hours Full Cure 2-3 Weeks
- l) Lowest Application Temperature 5 degrees C.
- m) Dry Recommended Application Thickness D.R.A.T. 295 Microns
- n) Methods Of Application Roller+Trowel Roller+ Texturing Air Spray Pressurised Pot
- o) Preparation See Preparation Sheet 1
- p) Storage Life One Year
- q) Thinner/Cleaner White Spirit
- r) Safety Ensure the use of good filter masks when spraying. The Use of Barrier Cream is recommended. DO NOT SMOKE or allow naked flames in the vicinity of work. Extreme care must be taken when spraying in enclosed areas. Supply Air Fed Masks.