



Technical Product Data

| | |
|---|--|
| Product Name | PLASBOND |
| Reference Number | P.P.4. |
| Product Description | An extremely durable and flexible product designed for maximum long term use on Masonry Substrates. Plasbond offers excellent adhesion and superior weather and water resistance, in addition to these benefits Plasbond has low dirt pick-up and is especially resistant to alkaline substrates and chalking. |
| Uses | An ideal product for both interior and exterior surfaces giving long term protection on Masonry substrates. |
| Pack Sizes | 5 and 10 Litres |
| Colour Range | Supplied on request. |
| Specific Gravity | 1.40 |
| Flash Point | N.A |
| Solids | 40% |
| Spreading Rate @ D.R.A.T | 3.00 Sq. Metres per litre - 2 coats. |
| Drying Time | 3 Hours |
| Overcoating Time | Not less than 8 hours |
| Lowest Application Temperature | 5°C |
| Dry Recommended Application Thickness D.R.A.T | 130 Microns from 2 coats. |
| Methods of Application | Brush, Roller and Spray. |
| Storage Life | 1 Year |
| Thinner / Cleaner | Water |
| Precautions | Protect from frost. |
| Safety | The use of a good filter mask is advised when spraying, splashes in the eyes must be washed out at once with plenty of clean water. |