



Technical Product Data

- a) **Product Name** **PVA BONDING COMPOUND**
- b) **Reference Number** P.P.28.
- c) **Product Description** This versatile product has been formulated for general usage in the building and decorative industry, in diluted form it can be used to stabilise porous substrates such as plaster, concrete, plasterboard etc. Use 5 parts water to 1 part P.V.A Bonding Compound. When bonding render coats for repair work pre-coat the area with 3 parts of the compound to 1 of water and apply the plaster before the compound dries. By adding equal amounts of water and the compound to the Mortar / Concrete mix a significant improvement in adhesion and tensile flexural strength will be achieved.
- d) **Uses** To enhance the adhesion of plaster render and mortar mixes.
- e) **Pack Sizes** 5 litre, 10 litre and 25 litre.
- f) **Specific Gravity** 1.03
- g) **Flash Point** N/A
- h) **Solids** 39.50
- i) **Drying Time** 3 hours
- j) **Overcoating Time** 30 minutes
- k) **Lowest Application Temperature** 5°C
- l) **Methods of Application** Normally by brushing
- m) **Storage Life** 12 Months
- n) **Thinner / Cleaner** Water
- o) **Precautions** Protect from frost
- p) **Safety** Refer to health and safety data sheet.