



Technical Product Data

a) Product Name	ROOFING SEALER
b) Reference Number	P.P.36.
c) Product Description	A solvent based vinyl acetate modified coating.
d) Uses	As a sealer / bonding agent over Bituminous Felt.
e) Pack Sizes	5 & 25 litre
f) Colour Range	Clear & White
g) Specific Gravity	0.86
h) Flash Point	Below 21°C
i) Solids	15% - 17%
j) Spreading Rate @ D.R.A.T	9sq Metres per litre
k) Drying Time	30 - 60 minutes at 20°C
l) Overcoating Time	16 - 24 hours
m) Lowest Application Temperature	5°C
n) Dry Recommended Application Thickness D.R.A.T	15 microns
o) Methods of Application	Brush, Roller and Spray
p) Recommended Preparation	See Preparation Data Sheet PP6
q) Storage Life	6 months
r) Thinner / Cleaner	Thinner PP44
s) Precautions	Do not smoke during application. Do not apply in wet weather. Do not apply inside a building.
t) Safety	Eye protection to B.S.2092, where splashing occurs wash with water for 10 minutes, if eyes affected seek medical attention. Use barrier cream - wash off with soap & water. Do not ingest or store near food or drink. Inhalation - if affected remove well away from work and rest.