

# PLASPERTEX PAINT CO LTD

## Technical Product Data sheet

03.12

Product Name	Plas-seal
Product reference	PP74
Product description	Clear water borne binding sealer for application to interior and exterior paving, concrete and stone. Application of Plas-seal enhances the colour of treated surfaces and increases resistance to wear and mild chemical attack. Additional coats will gradually increase sheen. If required, a slip resistant additive is available which can be added to the final coat of Plas-seal.
Uses	Penetrating binder/sealer for exterior paving, concrete and stone
Pack sizes availability	5 & 20 litres
Colour range	Clear
Specific gravity	Approx 1.0
Flash point	Non flammable
Recommended Spreading rate	Approx. 3 - 7 m <sup>2</sup> /litre depending on surface absorbency
Solids content	Approx 15% w/w
Drying time	Approx 1 hour 20°C 65%RH depending on level of penetration
Over-coating time	Approx 4 - 6 hours 20°C 65%RH
Minimum application temperature	Air and surface temperature should be 5°C and rising. Do not apply during damp or frosty weather or when rain is imminent
Recommended dry film thickness	N/A
Method of application	Brush, roller or low pressure spray.
Preparation	Surfaces must be clean, sound and dry and prepared in accordance with BS6150 Painting of buildings – code of practice. Treat organic growth with fungicidal solution. Remove weeds etc or treat with a proprietary herbicide
Storage life	Min 12 months in original sealed containers. Protect from frost and direct heat
Thinning/cleaning	Do not thin Wash equipment immediately after use with clean water and detergent.
Safety precautions	Refer to the safety data sheet before use
Volatile organic content (voc)	Limit for this product Cat A/h 30g/l (2010). This product contains maximum 25g/l VOC
Disposal	As supplied or containing liquid product – non hazardous waste code 08 01 12 waste paint and varnish other than those mentioned in 08 01 11 Used containers drained/rigorously scraped out and containing only dry residues: categorised as non-hazardous with waste code 15 01 02 (plastic package)  If mixed with other wastes the above waste codes may not be applicable

